

# Expression

A custom fit active wheelchair for image-conscious users in urban and semi-urban areas who are economically disadvantaged. Chair features light weight, super durability, transportability, extensive fit and positioning options, and a sleek urban look. Carries CE mark. Manufactured in factory with ISO 9000 quality system.



- Sweeping frame curves have sleek urban look similar to expensive chairs in the USA.
- Lighter weight than standard wheelchairs or rough terrain chairs for easy pushing.
- Versatile with a small footprint for maneuverability in tight places and speedy wheels on pavement and off. Works well in the office, local park, and on camping trips and traveling.
- Quick release wheels make chair easily transportable in cars.
- Strong enough for challenging environments. Durable bearings, wheels, and casters in standard easy-to-replace sizes. Strong enough to go up and down curbs every day.
- The best blend of style, affordability, and fit available today anywhere in the world.

Adjustability



Sleek curved design



Fold down back



Durability



|                                       | Small frame                   |                             | Medium frame                    |                             | Long Frame                  |                 |
|---------------------------------------|-------------------------------|-----------------------------|---------------------------------|-----------------------------|-----------------------------|-----------------|
| <b>Seat width</b>                     | 315mm (12 3/8")               | 355mm (14")                 | 355mm (14")                     | 395mm (15 1/2")             | 430mm (17")                 | 470mm (18 1/2") |
| <b>Seat depth</b>                     | 250mm–350mm (9 3/4"–13 3/4")  |                             | 330mm (13")–430mm (17")         |                             | 405mm (16")–505mm (19 7/8") |                 |
| <b>Front seat height</b>              | 420mm (16.5")–450mm (17 3/4") |                             | 440mm (17 3/8")–470mm (18 1/2") |                             | 480mm (18 7/8")–510mm (20") |                 |
| <b>Seat angle from ground</b>         | 4"                            |                             | 6"                              |                             |                             |                 |
| <b>Backrest height</b>                | 280 (11")–360 (14 1/8")       |                             | 280 (11")–360 (14 1/8")         | 360 (14 1/8")–440 (17 3/8") |                             |                 |
| <b>Backrest angle from seat sling</b> | 80°–120°                      |                             |                                 |                             |                             |                 |
| <b>Footrest height</b>                | 200–280mm (7 7/8"–11")        | 260–340mm (10 1/4"–13 3/8") | 260–360mm (10 1/4"–14 1/8")     | 330–410mm (13"–16 1/8")     |                             |                 |
| <b>Rear wheel camber angle</b>        | 4"                            |                             |                                 |                             |                             |                 |
| <b>Overall width</b>                  | 585mm (23")                   | 625mm (24 5/8")             | 625mm (24 5/8")                 | 665mm (26 1/8")             | 700mm (27 1/2")             | 740mm (29 1/8") |

**momentum**  
wheels for humanity

momentum4humanity.org